BelAirseries

www.timbucktoomfg.com
(310) 323-1134

A professional portable extractor with large capacity tanks. Easy access to components and ease of use.

Manufacturer of Commercial & Environmental Cleaning Equipment

Since 1974

© 2018 TIMBUCKTOO MFG, INC.

Specifications: (BELAIR-2204)

Moto

(2) 2 Stage vacuum motors[Part #: 11639200]

146" Water lift

107 CFM Air flow

Pump

120 PSI pump[Part #: 866-520-2141]

1.3 GPM Flow rate

Power

120 Volt AC / 17.5 Amps max

(1) 25' 12/3 Gauge power cord

Capacity

15 Gallon solution tank and 15 gallon recovery tank

Accessories Included:

(1) 25' vacuum hose & 25' solution hose assembly [Part#:TA1532594-4MF]

(1) Single jet, 12", Autoseal Wand[Part #: WMPT1V11008JG] (Patented heavy duty self-adjustable suction angle head with adjustable stainless steel grip handle)

Options:

Available with 170, 220, and 500 PSI pumps

(2) 3 Stage vacuum motors available

Output female plug

GFCI (ground fault circuit interrupter)

Pressure gauge

Auto fill and Auto dump system

Other Autoseal Wands available

Other hand tools and accessories available

Inline heater (210° F max) 🐔

For any specific custom options please contact customer service for availability

Shipping Weight

120 lb +

Exterior Dimensions

H 39" x W 21" x L 30"

Standard color

Light granite

Custom colors available please call customer service





Easy access to: switches, handle, drain hose, and all the mechanical parts.



CAUTION: Do not use flammable and volatile material

Comparison sheet in the back

BelAir Series

TIMBUCKTOO MFG., INC.

Soft Surface

BelAir Models				Compare to	
Model	BELAIR-2204	BELAIR-2304	BELAIR-2204H39	Rhino(RH-2500)	Whisper(W-249)
Vacuum Motor	(2) 2 Stage	(2) 3 Stage	(2) 2 Stage	(2) 2 Stage	(3) 2 Stage
Water Lift	146"	203"	146"	146"	249"
Air Flow	107 CFM	107 CFM	107 CFM	107 CFM	108 CFM
		Pumps			
60 PSI - TMI Brand	-	-	-	0	0
100 PSI - Shurflo	-	-	-	О	0
120 PSI - TMI Brand	S	S	S	s	S
170 PSI - TMI Brand	0	0	0	О	0
220 PSI - TMI Brand	0	0	0	О	0
500 PSI - Pumptec	0	0	0	О	0
500 PSI - Cat Pump	0	0	0	О	0
·		Power			
120 Volts	S	S	S	S	S
240 Volts	0	0	0	О	0
Max Amps	17.5	13.5/14.5	17.5/7	17.5	18.5/8.5
•	Vacuui	m/Solution Ho	se Lengths		
10 ft / 10 ft	-	-	-	-	-
15 ft / 15 ft	-	-	-	-	-
25 ft / 25ft	S	S	S	s	S
50 ft / 50 ft	0	0	0	0	0
		Wands			
Autoseal 1-Jet	S	S	S	S	S
Autoseal See Throu 1-Jet	0	0	0	o	0
Autoseal Double Bend 1-Jet	0	0	0	o	0
Autoseal 2-Jet	0	0	0	О	0
Autoseal See Throu 2-Jet	0	0	0	o	0
Autoseal Double Bend 2-Jet	0	0	0	О	0
	V	Wheels and Cas	sters	,	
(2) 4" Casters and (2)12" Wheels	S	S	S	NA	NA
(2) 4" Casters and (2) 12" Wheels	NA	NA	NA	NA	S
(2) 3" Casters and (2) 10" Wheels	NA	NA	NA	s	NA
Other Options					
Intank Heater	NA	NA	NA	NA	NA
Inline Heater	0	0	0	О	0
Stationary Handle	S	S	S	s	S
-	Dir	nensions and \	Weight	,	
Solution / Recovery Tank Capacity	15/15 Gallon	15/15 Gallon	15/15 Gallon	11/13Gallon	13/15 Gallon
Dimensions of Machine Only	39"x21"x30"	39"x21"x30"	39"x21"x30"	36"x21"x28"	37"x22"x30"
Weight of Machine Only	85 lb	105 lb	105 lb	69 lb	
Shipping Dimensions of Machine and Hose	42"x22"x30"	42"x22"x30"	42"x22"x30"	42"x22"x30"	42"x22"x30"
Shipping Weight of Machine and Hose	120 lb	120 lb	120 lb	98 lb	140 lb
Shipping Dimensions of Wand	13"x13"x66"	13"x13"x66"	13"x13"x66"	13"x13"x66"	13"x13"x66"
Shipping Weight of Wand	13 lb	13 lb	13 lb	13 lb	13 lb